

N G 5 N



20.5×7.2×15.3

Features

- Small size, light weight.
- Switching capacity up to 5A.
- Low coil power consumption 0.2W.
- Suitable for household electrical appliance, automation system, electronic equipment, instrument, meter, telecommunication facilities and remote control facilities.

Contact Data

Contact Arrangement	1A	
Contact Material	Silver Alloy	
Contact Rating (resistive)	5A/30VDC,250VAC	
Max. Switching Power	150W 1250VA	min Switching load:10mA/5V
Max. Switching Voltage	30VDC 250VAC	Max. Switching Current:5A
Contact Resistance or Voltage drop	≤100mΩ	Item 3.12 of IEC255-7
Operation life	Electrical	10 ⁵ Item 3.30 of IEC255-7
	Mechanical	10 ⁷ Item 3.31 of IEC255-7

CAUTION:

Relays previously tested or used above 10mA resistive at 6VDC maximum or peak AC open circuit are not recommended for subsequent use in low level applications.

Coil Parameter

Coil voltage VDC		Coil resistance Ω±10%	Pickup voltage VDC(max) (75%of rated voltage)	release voltage VDC(min) (10% of rated voltage)	Coil power consumption W	Operate Time ms	Release Time ms
Rated	Max.						
3	3.9	45	2.25	0.3	0.2	≤10	≤4
5	6.5	125	3.75	0.5			
6	7.8	180	4.50	0.6			
9	11.7	405	6.75	0.9			
12	15.6	720	9.00	1.2			
18	23.4	1620	13.5	1.8			
24	31.2	2880	18.0	2.4			

CAUTION: 1.The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.

2.Pickup and release voltage are for test purposes only and are not to be used as design criteria.

Operation condition

Insulation Resistance	1000MΩ min (at 500VDC)	Item 7 of IEC255-5
Dielectric Strength		
Between contacts	50Hz 750V	Item 6 of IEC255-5
Between contact and coil	50Hz 4000V surge voltage:7kV	Item 6 and 8 of IEC255-5
Shock resistance	Functional:100m/s ² 11ms Endurance:1000m/s ² 6ms	IEC68-2-27 Test Ea
Vibration resistance	10~50Hz Functional & Endurance double amplitude 1.5mm	IEC68-2-6 Test Fc
Terminals strength	5N	IEC68-2-21 Test Ua1
Solderability	230℃±2℃ 10±0.5s	IEC68-2-20 Test Ta method 1
Ambient Temperature	-30~70℃	
Relative Humidity	20%~85% (at 40℃)	IEC68-2-3Test Ca
Mass	4g	

Qualification inspection:

Perform the qualification test as specified in the table IV of IEC255-19-1 and minimum sample size 24.

Ordering Information			
NG5N	A	DC12V	
			Coil rated DC Voltage 3V, 5V,6V, 9V, 12V,18V, 24V
			Contact Arrangement A:1A
Part number: NG5N			

Dimensions (Unit: mm)				
	mm	inch		
		0.27	0.011	
		0.52	0.020	
		0.8	0.031	
		1.05	0.041	
		1.1	0.043	
		1.2	0.047	
		3.4	0.134	
		4.7	0.185	
		7	0.275	
		7.2	0.283	
		11.5	0.453	
	15.3	0.602		
	20.5	0.807		
Dimensions				
Mounting (Bottom views)				
Wiring diagram (Bottom views)				

NOTES 1).Dimensions are in millimeter.
2).Inch equivalents are given for general information only.